

## Economical Dual Bus Control System

Crestron 2-Series Control Systems are the brain of a complete integrated AV or automation solution. Every audio, video, and environmental element of the home, boardroom, classroom, or command center becomes integrated and accessible through the control system. Crestron 2-Series control systems are unmatched for power, performance and scalability, providing the ideal choice for today's demanding control applications.

The AV2 is designed for medium to large-scale commercial and residential control applications. Six built-in COM ports, eight IR/Serial ports, eight I/O Versiports, eight isolated relays, and optional Ethernet provide the essential interface for control of numerous devices including video projectors, plasma displays, switchers, DVD players, screens, lifts, and much more. The AV2 features a built-in power supply, with power available to support external Cresnet devices including touchpanels, keypads and expansion modules.

### 2-Series Engine

At the heart of the AV2 is the powerful 32-bit Freescale ColdFire® processor. Crestron's exclusive enhanced real-time operating system makes the AV2 the fastest, most reliable control system available.

### Dual Bus Architecture

The AV2's unique dual-bus architecture affords ultra fast communications. The 40Mbps Y-Bus provides a high-speed backplane for IR, serial, and other integrated control ports. Additional control ports and interfaces like MIDI and digital audio processing may be added by installing up to three Y-Bus control cards (expansion cage option required). At a blazing 300Mbps, the Z-Bus supports Fast Ethernet with future support for other emerging technologies.

### Cresnet®

Cresnet is the communications backbone for many Crestron touchpanels, keypads, lighting controls, and other devices. The Cresnet bus is a simple, yet flexible 4-wire network that provides rock-solid bidirectional communication and power for up to 252 Cresnet devices.

### Cresnet Slave Mode


Selectable Cresnet Slave Mode enables the AV2 to be configured as a Cresnet slave device, effectively transforming it into a Cresnet expansion module. Such flexibility can offer a cost-effective solution for system expansion, providing a host of additional control ports in a single module.

### Ethernet

Crestron pioneered the IP-based control system to harness the vast possibilities of Ethernet and the Internet for remote control, monitoring, programming, and diagnostics, and the AV2 is designed to deliver the world's most advanced IP control solution. A choice of single or dual port Ethernet cards enables a full-duplex 10/100 Ethernet connection with built-in Web server and email client, and support for both static and dynamic IP addressing.

### e-Control@2

Crestron's award-winning e-Control 2 XPanel solutions offer the most flexible range of IP control possibilities available. Using a Windows® computer or CE/PocketPC™ PDA device, e-Control 2 provides an amazing control GUI that looks and behaves just like a Crestron Isys® touchpanel.



### RoomView™

Every Ethernet-enabled 2-Series control system works directly with Crestron's exclusive RoomView Help Desk software for the industry's most comprehensive facility-wide asset management solution.

### SNMP

Built-in SNMP support enables network management of Crestron control systems using third-party SNMP software. As an alternate or supplement to RoomView, SNMP allows full control and monitoring from the IT Help Desk or NOC in a format that's familiar to IT personnel.

### SSL

All Ethernet-enabled 2-Series control systems support SSL (Secure Sockets Layer), the industry standard for protecting sensitive network communications.

### NAT

The AV2's onboard NAT (Network Address Translator) acts as a firewall and router to facilitate the configuration of a private control LAN with a single-point connection to the client's LAN (Dual-port Ethernet card required).

### Memory Expansion

A memory card slot accessible on the rear panel allows for easy expansion of the AV2's internal memory using any Type II Compact Flash memory card up to 2 GB.

> [2-Series engine | Dual-bus architecture](#)

> [Compact Flash memory card slot](#)

> [Cresnet port - master/slave selectable](#)

> [10/100 Ethernet capable | SSL encryption](#)

> [e-Control 2 and RoomView enabled](#)

> [SNMP support | Built-in firewall, NAT and router](#)

> [6 Com ports, 8 IR/serial ports, 8 Versiport I/O ports, 8](#)

# AV2 Economical Dual Bus Control System

## Relay ports

> 3 Y-Bus / 1 Z-Bus control card expansion slots

> Internal power supply | 2-Space EIA rack-mountable

## SPECIFICATIONS

### Processor

CPU: 32-bit Freescale ColdFire® Microprocessor

### Memory

SDRAM: 64 MB

NVRAM: 256 KB

Flash: 4 MB

Compact Flash: expandable up to 2 GB (not included)

### Operating System

Real-time, preemptive multi-threaded/multitasking kernel; FAT32 file system with long names; supports SIMPL™ Windows® and SIMPL+®

### Ethernet

With C2ENET-1: 10/100BaseT, auto-negotiating, full/half duplex, static IP or DHCP/DNS, SSL, TCP/IP, UDP/IP, CIP, SMTP, SNMP, built-in Web server and e-mail client; supports Crestron e-Control®2 XPanel and RoomView™ applications

With C2ENET-2: All above features plus: built-in firewall, router, and network address translator (NAT)

### Y-Bus Connectors & Expansion Slots

40 Mb/s parallel communications;

Internal backplane for integrated control ports and Y-Bus expansion slots

COM A - F: (6) DB9 male, bidirectional RS-232/422/485 ports;

Up to 115.2k baud;

Hardware and software handshaking support;

Ports C-F support C2N-NPA8 Network Poll Accelerator

INFRARED-SERIAL OUTPUT A - H: (8) 2-pin 3.5mm detachable terminal blocks, IR/Serial output ports;

IR output up to 1.2 MHz;

1-way serial TTL/RS-232 (0-5 Volts) up to 115.2k baud;

Individual signal generator per port, allowing simultaneous firing of all ports

I/O Versiports 1 - 8: (1) 9-pin 3.5mm detachable terminal block comprising

(8) digital input/output or analog input ports (referenced to GND);

Digital Input: Rated for 0-24 Volts DC, input impedance 20k ohms, logic threshold 1.24 Volts DC;

Digital Output: 250mA sink from maximum 24 Volts DC, catch diodes for use with "real world" loads;

Analog Input: Rated for 0-10 Volts DC, protected to 24 Volts DC maximum, input impedance 20k ohms;

Programmable 5 Volts, 2k ohms pull-up resistor per pin

RELAY OUTPUT 1 - 8: (2) 8-pin 3.5mm detachable terminal blocks

comprising (8) normally open, isolated relays;

Rated 1 Amp, 30 Volts AC/DC;

MOV arc suppression across contacts

Expansion Slots: (3) Y-Bus expansion slots (Requires CAGE2 accessory, sold separately);

Accept all Y-Bus control cards

### Z-Bus Expansion Slots

300 Mb/s parallel communications;

Backplane for Z-Bus expansion slots

Expansion Slot: (1) Z-Bus expansion slot;

Accepts all Z-Bus control cards

### Additional Connectors

COMPUTER: (2) DB9 female;

Front and rear panel RS-232 computer console ports

NET: (1) 4-pin 5mm detachable terminal block;

Cresnet port, Master/Slave selectable;

Expandable via C2N-NPA8 Network Poll Accelerator

100-250V~2.3A

50/60 Hz(1) IEC Socket;

Mates with removable power cord, included

Ground: (1) 6-32 screw, chassis ground lug

### Reset Buttons

HW-R: Hardware reset (reboots the control system)

SW-R: Software reset (restarts the SIMPL program)

### LED Indicators

PWR: (1 green) Indicated AC power supplied to unit

NET: (1 yellow) Indicates Cresnet bus activity

MSG: (1 red) Indicates control system has generated an error message

LNK A: (1 red) Indicates a valid connection on LAN port A

ACT A: (1 red) Indicates activity on LAN port A

LNK B: (1 red) Indicates a valid connection on LAN port B

ACT B: (1 red) Indicates activity on LAN port B

### Power Requirements

Main Power : 2.3 Amps, 100-250 Volts AC, 50/60 Hz

Available Cresnet Power: 50 Watts (shared with control card expansion slots)

### Environmental

Temperature: 41° to 113°F (5° to 45°C)

Humidity: 10% to 90% RH (non-condensing)

### Enclosure

Chassis: Steel, black matte powder coat finish

Faceplate: Extruded aluminum, black matte powder coat finish with polycarbonate label overlay

Mounting: Freestanding or 2U 19-inch rack-mountable (adhesive feet and rack ears included)

### Dimensions

Height: 3.56 in (9.04 cm);

3.47 (8.81 cm) without feet

Width: 17.03 in (43.26 cm);

19.0 in (48.26 cm) with ears

Depth: 10.31 in (26.19 cm)

### Weight

7.1 lb (3.22 kg) - with line cord

### Available Models

AV2: Economical Dual Bus Control System

### Available Accessories

C2COM-2: 2 Port RS-232/422/485 Card for Y-Bus Expansion Slot

C2COM-3: 3 Port RS-232/422/485 Card for Y-Bus Expansion Slot

C2ENET-1: Single Port Ethernet Card for Z-Bus Expansion Slot

C2ENET-2: Dual Port Ethernet Card for Z-Bus Expansion Slot

C2IR-8: 8 Port Infrared/Serial Output Card for Y-Bus Expansion Slot

C2N-HBLOCK: Multi-type Cresnet Distribution Block

# AV2 Economical Dual Bus Control System

**C2N-NPA8:** Cresnet Network Poll Accelerator  
**C2N-SPWS300:** Cresnet Power Supply, 300 Watts  
**C2N-VEQ4:** 4-Channel Volume/EQ Control Module  
**CAGE2:** 3-Card Y-Bus Expansion Cage for AV2  
**CNSP-XX:** Custom Serial Interface Cable  
**CNXAO-8:** 8 Analog Output Card for Y-Bus Expansion Slot  
**CNXIO-16:** 16 Port Versiport Card for Y-Bus Expansion Slot  
**CNXMIDI:** MIDI Interface Card for Y-Bus Expansion Slot  
**CNXRY-16:** 16 Relay Card for Y-Bus Expansion Slot  
**CNXRY-8:** 8 Relay Card for Y-Bus Expansion Slot  
**IRP2:** IR Emitter Probe